Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	LUTEC
--------------------------------	-------

Supplier's address: LUTEC EUROPE NV, Herentalsebaan 425, 2160 Wommelgem Wommelgem, BE

Model identifier: 51	189102032IVI
----------------------	--------------

_	•			
Tyna	Λt	lioht	source	٠.
IVDE	vı	HEILL	JUUILE	- •

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	Welding		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

		Troduct parar	1101013	
Parameter		Value	Parameter	Value
General product parameters:				
0,	mption in on- 100 h), rounded st integer	11	Energy efficiency class	F
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	1 000 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode pexpressed in W	oower (P _{on}),	10,5	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
for CLS, expre	dby power (P _{net}) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	12	Spectral power	See image
dimensions	Width	30	distribution in the	in last page
without	Depth	118		
				D 1 / 2

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	72
		Chromaticity	0,380
		coordinates (x and y)	0,380
Parameters for LED and OLED lig	tht sources:		
R9 colour rendering index value	6	Survival factor	1,00
the lumen maintenance factor	0,96		
Parameters for LED and OLED mains light sources:			
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	-

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

