Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name	or trade mark:	LUTEC
-----------------	----------------	-------

Supplier's address: LUTEC EUROPE NV, Herentalsebaan 425, 2160 Wommelgem Wommelgem, BE

_	•		
Typa	Ot.	liaht	source:
IVDE	UI.	IIKIIL	source.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	Welding		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Parameter		Value	Parameter	Value
		General product p	arameters:	
	mption in on- 100 h), rounded st integer	21	Energy efficiency class	F
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	2 200 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode pexpressed in W	oower (P _{on}),	21,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
for CLS, expres	dby power (P _{net}) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	15	Spectral power	See image
dimensions	Width	34	distribution in the	in last page
without	Depth	197		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)		Yes	If yes, equivalent power (W)	136
			Chromaticity	0,440
			coordinates (x and y)	0,403
Parameters for LI	ED and OLED lig	ht sources:		
R9 colour renderi	ing index value	11	Survival factor	1,00
the lumen maintenance factor		0,96		
Parameters for LED and OLED mains light sources:				
displacement fac	tor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6
Claims that a source replaces light source with ballast of a partic	out integrated	_(b)	If yes then replacement claim (W)	-
Flicker metric (Ps	t LM)	1,0	Stroboscopic effect metric (SVM)	1,0

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

