## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LUTEC	
--------------------------------------	--

Supplier's address: LUTEC EUROPE NV, Herentalsebaan 425, 2160 Wommelgem Womme
---

Model	identifier:	7193001118M
IVIUUEI	iuciiliici.	1 TOOUTTTOIN

_	•			
Typa	Λt	liaht	source	•
IVDE	VI.	HEILL	<b>3</b> Uul CE	

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	Welding		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

## Product parameters

Parameter		Value	Parameter	Value
General product parameters:				
	mption in on- 100 h), rounded st integer	18	Energy efficiency class	E
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	1 905 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power (P <sub>on</sub> ), expressed in W		17,3	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	15	Spectral power	See image
dimensions	Width	80	distribution in the	in last page
without	Depth	177		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load		
Claim of equival	ent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	121	
			Chromaticity	0,440	
			coordinates (x and y)	0,403	
Parameters for	LED and OLED lig	ht sources:	'		
R9 colour rende	ring index value	11	Survival factor	1,00	
the lumen maintenance factor		0,96			
Parameters for	Parameters for LED and OLED mains light sources:				
displacement fa	ctor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6	
Claims that source replaces light source with ballast of a parti	hout integrated	_(b)	If yes then replacement claim (W)	-	
Flicker metric (P	st LM)	1,0	Stroboscopic effect metric (SVM)	1,0	

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

