## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

ι	
	Supplier's name or trade mark: LUTEC

_	•			
Tyna	Λt	lioht	source	٠.
IVDE	vı	HEILL	JUUILE	- •

LED	Non-directional or directional:	NDLS
E27		
MLS	Connected light source (CLS):	Yes
No	Envelope:	-
No		
No	Dimmable:	Yes
	E27 MLS No No	MLS Connected light source (CLS):  No Envelope:  No

## **Product parameters**

1 Todaet parameters				
Parameter		Value	Parameter	Value
General product parameters:				
	mption in on- 100 h), rounded st integer	8	Energy efficiency class	Е
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	835 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	22005500
On-mode prespressed in W	oower (P <sub>on</sub> ),	7,5	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,50
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		0,50	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	175	Spectral power	See image
dimensions	Width	125	distribution in the	in last page
without	Depth	125	1	

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load	
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	62
		Chromaticity	0,440
		coordinates (x and y)	0,403
Parameters for LED and OLED light sources:			
R9 colour rendering index value	10	Survival factor	1,00
the lumen maintenance factor	0,96		
Parameters for LED and OLED mains light sources:			
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

